



INVENTO SX30 3T - Mobile scissor lift







INVENTO SX30 is a mobile scissor lift with a 3-ton lifting capacity and a maximum lifting height of up to 1,185 mm (plus adapters).

Description

INVENTO SX30 is a mobile scissor lift with a 3-ton lifting capacity and a maximum lifting height of up to 1,185 mm (plus adapters). It is a professional solution designed for servicing passenger cars and light commercial vehicles. Thanks to its construction, it is perfectly suited for tyre-related work, brake system service, as well as mechanical and bodywork repairs.

Note: The lift is designed for vehicles with a maximum wheelbase of 2.7 - 3 m (depending on the arrangement of the support points)!

The device's greatest advantage is its full mobility. The specially designed control trolley also functions as a drawbar, allowing the lift to be moved easily and enabling flexible workshop space arrangement without the need for permanent floor installation. This makes it possible to create a temporary, fully functional work station anywhere in the workshop hall.

The lift is a surface-mounted device—its installation does not require any special excavations or foundations, which significantly reduces workshop installation costs.

Safety:

The lift is equipped with a mechanical safety lock. The system is designed to remain in the secured position throughout its entire operation.

Work efficiency is enhanced by four independently adjustable lifting arms with a length of 690 mm, which, combined with adjustable lifting pads, allow precise positioning of lifting points for almost any vehicle.

Main product features:

- 3-ton lifting capacity allowing service of a wide range of vehicles.
- Full mobility thanks to the integrated transport kit.
- Solid, compact construction ensuring long-term durability in workshop conditions.
- Intuitive control unit with an ergonomic height (1208 mm).
- Work safety ensured by the automatic mechanical lock.
- Versatility – adjustable arms and adapters allow servicing vehicles with different support point spacing.
- CE certificate confirming compliance with European safety standards.

Technical data:

- Capacity: 3,000 kg
- Maximum lifting height: 1185 mm
- Minimum height (clearance): 124 mm
- Platform width: 1055 mm
- Frame length: 1523 mm
- Total length: 1800 mm
- Lifting arm length: 690 mm
- Adapter height: 102 mm + 40 mm (pads)
- Control unit dimensions: height 1208 mm / width 305 mm
- Motor power: 2.2 kW
- Power supply: 230V
- Lifting / lowering time: 30 s
- Weight: 430 kg

Technical data

5906288320401

Parameter	Data
Capacity	3,000 kg
Maximum lifting height	1185 mm
Minimum height (clearance)	124 mm
Platform width	1055 mm
Frame length	1523 mm
Total length	1800 mm
Lifting arm length	690 mm
Adapter height	102 mm + 40 mm (pads)
Control unit dimensions	height 1208 mm / width 305 mm
Motor power	2.2 kW
Power supply	230V
Lifting / lowering time	30 s
Weight	430 kg

Warranty: 12 months

